Technical Data Sheet



AR-92

Asphalt Release Agent

AR-92 is a water soluble release agent which prevents asphalt from sticking to the sides and bottom of truck beds. Proper application produces a rich foam which allows asphalt loads to easily slide from truck beds when tilted. Will not affect the composition of the asphalt mix.

Directions for Use

AR-92 is dispensed through standard proportioning valves. Standard dilution is 40 parts of water to 1 part AR-92.

Surface treated must be clean of any asphalt accumulation. Apply solution to sides, bed and spreader bar of the truck. For best results, fill truck with asphalt while the coating is still wet.

Safety Reminder

Consult Product Label and Safety Data Sheet (SDS) before use. Prior to using this or any cleaning product, make sure employees read and understand the hazard information found on the product label and Safety Data Sheet (SDS). The label and SDS will also provide information on handling precautions, protective equipment and first aid instructions which might be appropriate for this product.

Distributor

Brewer Cote of Arizona The Pavement Maintenance Specialists 5226 W Missouri Avenue, Glendale, Arizona 85301 www.brewercoteaz.com 888-931-3728 sales@brewercoteaz.com



Technical Specifications

Appearance
Odor
pH (1% solution, 22°C)
Foaming
Flash Point
Rinsability
Stability/Storage
Emulsification
Solubility
Phosphate Content

Product Number

G5-55

Yellow Liquid Mild

7-8 High None

Complete 2 Years

Complete 100%

None

Packaging 55 Gallon Drum

Technical Data Sheet



PEC

Paving Equipment Cleaner

Paving Equipment Cleaner is a heavy duty cleaner that can be used on a variety of asphalt related equipment to include:

Truck Beds Racks & Shovels Paving Machines Rollers & Spreader Bars Wheelbarrows

Paving Equipment Cleaner is a ready to use product that can also be used to coat tools and equipment prior to use to keep them free of build-up.

Directions for Use

Spray, wipe or brush the object to be cleaned with PEC. Small objects may also be immersed, if desired. Allow cleaner to remain on surface until the asphalt is loosened.

Safety Reminder

Consult Product Label and Safety Data Sheet (SDS) before use. Prior to using this or any cleaning product, make sure employees read and understand the hazard information found on the product label and Safety Data Sheet (SDS). The label and SDS will also provide information on handling precautions, protective equipment and first aid instructions which might be appropriate for this product.

Distributor

Brewer Cote of Arizona The Pavement Maintenance Specialists 5226 W Missouri Avenue, Glendale, Arizona 85301 www.brewercoteaz.com 888-931-3728 sales@brewercoteaz.com



Technical Specifications

Appearance
Odor
pH
Foaming
Flash Point
Rinsability
Stability/Storage
Emulsification
Solubility
Phosphate Content

Product Number

G9-4CS G9-5G G9-55 Clear Liquid Slight odor N/D None 159.8F Complete 2 Years Complete 100% None

Packaging

4 Gallon Case 5 Gallon Pail 55 Gallon Drum

Technical Data Sheet



Solvit

Tar & Asphalt Remover

A d-limomene based heavy duty degreaser & tar remover. Specially formulated with natural citrus based oils. Excellent for all cleaning tasks. Emulsifies and quickly removes grease & grime. Great for use on tools and equipment, flooring, siding and sidewalks.

Directions for Use

USAGE: Application and coverage rate will vary depending on conditions. FIRST AND FOREMOST Solvit should be used full strength. For hard surfaces such as concrete, metal, wood, glass, ceramic and stone, the object may be sprayed, poured, brushed, blotted or soaked. Allow time for product to work, then agitate with a rag or stiff bristle brush and rinse away stain and residue with water. Repeat as needed. Thicker soils can be scraped to remove heavy deposits prior to application. Tools and equipment must be solvent resistant. NOTE: Objects to be cleaned should first be tested for compatibility, especially on paints and plastics. Do not use on plastic surfaces unless they are solvent resistant.

Safety Reminder

Consult Product Label and Safety Data Sheet (SDS) before use. Prior to using this or any cleaning product, make sure employees read and understand the hazard information found on the product label and Safety Data Sheet (SDS). The label and SDS will also provide information on handling precautions, protective equipment and first aid instructions which might be appropriate for this product.

Distributor

Brewer Cote of Arizona The Pavement Maintenance Specialists 5226 W Missouri Avenue, Glendale, Arizona 85301 www.brewercoteaz.com 888-931-3728 sales@brewercoteaz.com



Technical Specifications

Appearance Odor pH Foaming Flash Point Rinsability Stability/Storage Emulsification Solubility Phosphate Content

Product Number

G8-QCS G8-4CS G8-5G G8-55 Citrus N/D None 115.4 F Complete 2 Years Complete 100% None

Orange Liquid

Packaging

12 Quart Case 4 Gallon Case 5 Gallon Pail 55 Gallon Drum



SOLVALL

Tar & Asphalt Remover

Solvall is a ready-to-use, water rinsable liquid, which quickly and easily removes coal tar sealer, asphalt sealer, crack sealer, roofing tar, mastic and tack coat from most washable surfaces. Formulated for use on tools, equipment, vehicles, sidewalks, flooring, siding, clothing and carpeting. Will breakdown the composition of the stain and emulsify so that it is rinsed away with water. It is non-foaming and evaporates slowly. SOLVALL will clean up fresh spills, splatters and oversprays, as well as, caked-on messes.

Directions for Use

USAGE: Application and coverage rate will vary depending on conditions. FIRST AND FOREMOST Solvall should be used full strength. For hard surfaces such as concrete, metal, wood, glass, ceramic and stone, the object may be sprayed, poured, brushed, blotted or soaked. Allow time for product to work, then agitate with a rag or stiff bristle brush and rinse away stain and residue with water. Repeat as needed. Thicker soils can be scraped to remove heavy deposits prior to application. Tools and equipment must be solvent resistant. NOTE: Objects to be cleaned should first be tested for compatibility, especially on paints and plastics. Do not use on plastic surfaces unless they are solvent resistant.

Safety Reminder

Consult Product Label and Safety Data Sheet (SDS) before use. Prior to using this or any cleaning product, make sure employees read and understand the hazard information found on the product label and Safety Data Sheet (SDS). The label and SDS will also provide information on handling precautions, protective equipment and first aid instructions which might be appropriate for this product.

Distributor

Brewer Cote of Arizona The Pavement Maintenance Specialists 5226 W Missouri Avenue, Glendale, Arizona 85301 www.brewercoteaz.com 888-931-3728 sales@brewercoteaz.com



Technical Specifications

Appearance
Odor
pH
Foaming
Flash Point
Rinsability
Stability/Storage
Emulsification
Solubility
Phosphate Content

Product Number

G11-QCS G11-4CS G11-5G G11-55 Clear Liquid Characteristic N/D

None 118.4 F Complete 2 Years Complete 100% None

Packaging

12 Quart Case 4 Gallon Case 5 Gallon Pail 55 Gallon Drum

WATER JEL®

"4 x 4"

BURN DRESSING

(Part Number 450615)

"Whenever a burn emergency strikes, we've got the dressing to match it"
For Burn Relief of Painful Burns, Water Jels ® got you Covered!

Regardless of your industry a burn can strike at any time and that why it is so important to be prepared. Any burn, even a minor one, can be extremely painful and dangerous.

In treating a burn emergency, speed and portability are key. Consisting of a scientifically formulated cooling gel and medical grade non-woven carrier, when applied to the wound, these burn dressings cool the burn, relieve the pain and protect against airborne contamination. Water based and water soluble, Water Jel® Sterile Burn Dressings won't stick to the wound and may be applied directly over clothing.

Packed in individual foil pouches, Water Jel ® Sterile Burn Dressings are available in different sizes to accommodate a variety of emergency situations.

With Water Jel ® Sterile Burn Dressing, it takes no special training to give fast and effective burn care for any type of burn injury.

Sizes Available
2"x 6" (5x15 cm) 4"x 16" (10x40 cm)
8"x 18" (20x46 cm) 12"x 16" (30.5x40.5 cm)
Standard in Stock
4"x 4" (10x10 cm)

10% Discount on purchase of 1 box (15 each)

BREWER COTE
of Frizona
The Pavement Maintenance Specialist
226 W. MISSOURI AVENUE, GLENDALE, AZ 8531

5226 W. MISSOURI AVENUE, GLENDALE, AZ 85301 Tel. 623-931-3728 Toll 888-931-3728 Fax 623-842-0714 www.brewercoteaz.com sales@brewercoteaz.com




Check Out the Rest - But Buy the Best

LAB Manufacturing-Engineering Combustion Systems for Over a Decade



Quick Connect Fittings



- △ Patented "Flame Free" Combustion system properly cleans and dries Asphalt and Concrete Cracks, Joints and Potholes in one easy step
- △ High Velocity Hot Air quickly prepares Sealant reservoir maximizing sealant adhesion
- △ No Flame means no Surface Impingement cleans and dries faster than conventional torches
- △ In Seconds, the Hot Air Lance dries, cleans and prepares cracks / joints for sealant application
- △ Precision Engineered to outperform the competition
- △ Balanced for One-handed use, Anyone can be taught to be a skillfull operator in a matter of minutes
- ▲ Adjustable Temperature / Volume Controls for maximum effectiveness and economy
- ▲ Built with Pride in the USA

The Best Hot Air Lance in the Industry for Drying and Cleaning Pavement Cracks, Joints and Potholes



LAB Hot Air Lances blast out dirt & debris with Hot Compressed Air. They Draw out moisture from cracks without "over cooking"; lifting off oxidized surface leaving a warm, dry surface, properly prepared sealant adhesion.

Hot Air dries more thoroughly because it expands surfaces faster under any conditions, particularly inclement weather. Unlike flame, Hot Air completely extracts moisture leaving smooth, clean surfaces that are ready for sealant application

Patented Combustion System for guaranteed performance

Rugged Stainless Steel Construction for years of trouble free operation



We at LAB are committed to providing you, the Customer, the best and most versatile Hot Air Lance in the industry. This Lance is an integral part of the whole package and may be purchased by itself.

However, we offer a complete kit which includes everything you need to conduct your business in the most efficient, economical and profitable way possible. All you need is an air compressor and propane tank to begin successful operation.

How does A Hot Air Lance Work?

Lab Heat Lances burn vapor propane and mix it with super-heated compressed air in a specially designed and patented combustion chamber. High velocity hot air is produced and directed towards the pavement surface. Since no flame touches the pavement, you can fill cracks immediately behind the lance operator without the worry of burning or charring the pavement surface

Which Model Suits You?

In order to produce enough velocity, you must have a good air supply of compressed air to effectively and Quickly clean and dry pavement cracks, joints and potholes. The more air you provide the better the performance. Which lance is right for you? The major difference is the volume of air-supply. What size is your compressor? Use chart for reference.

Compressor Size 60 – 100 cfm 100 – 185 cfm 150+ cfm Best Performance
Hot Shot
Classic Model B
Blaster Model C

Complete Package Includes

Hot Air Lance Unit (Hot Shot - Classic - Blaster) Hose Assembly/ Cover (40'-50'-60') Shoulder Strap Heavy Duty Air Filter
LP Regulator & Gauge
Quick Connect Fittings
Safety & Operation Manual
Warranty Card





Hot Shot

Heated Air Temperatures Exit Heated Air Propane Propane Consumption Compressed Air Supply BTU's Lance Weight 400°- 2600° F Up to 1000 ft/sec 5 to 30 psi 10 lbs/hr @ 20 psi 60-100 cfm / 50-175 psi to 1,000,000 11 lbs

Classic B

400°- 2600° F Up to 1000 ft/sec 5 to 30 psi 10 lbs/hr @ 20 psi 100-185 cfm / 50-175 psi to 1,000,000 11 lbs

Blaster C

600° - 3000° F Up to 3000 ft/sec 5 to 30 psi 12 lbs/hr @ 20 psi 150+ cfm / 90-175 psi to 1,500,000 12 lbs

Stinger All-in-One

A portable crack sealing lance in one package

Features

Honda GX 5.5 HP Engine
Electronic Ignition
Stainless Steel Burner
Easy to Operate Swivel Rear Wheel
Lance Assembly weight 10 lbs
Lance Assembly Length 59"
Single Stage Compressor
40"H x 39"W x 51"L
Shipping Weight 280 lbs

CAT Torch Kit

Save Money on this Lower budget Unit

Lightweight Aluminum Body
Fingertip Control for Air & Fuel
Includes Propane Hose (50ft) & Regulator
Cleans & Dries with High Temperature
Extends your work season
BTU rating – 300,000 @ 55 psi
Temp Output – 2000°-2400°
Use with Your own Air
Compressor & Propane Tank

The Hottest Thing On The Road

Be Sure You Get The FACTS

We're Honored that you are considering our High-Performance Flame-Free Equipment. LAB Prides itself on its patented flame free combustion system. Be Sure that you do your research When inquiring about other heat lances. Some claim to be "Flame Free" but proof is the key. Get a demo of each and witness the difference in LAB Heat Lances from the other "so called" heat lances on the market. You'll be glad you did! Don't get burned by look-a-likes.

Additional Uses for Our Heat Lances

Pothole Preparation prior to Filling
Dry Pavement Surfaces prior to Line Striping
Removal of Thermoplastic and Water based Paint
Remove / Re-Melt excess sealant material from Pavement
Dry concrete surfaces prior to application of coatings
Reflector casting removal



Each Unit is Performance Tested at Factory. Fully Guaranteed against Material and Manufacturing Defects Distributed by
Brewer Cote of Arizona
The Pavement Maintenance Specialists
5226 W. Missouri Ave, Glendale AZ 85301
Tel. 623-931-3728 Toll 888-931-3728
www.brewercoteaz.com
sales@brewercoteaz.com

The New, Stronger LITTLE WONDER'S OPTIMAX BLOWERS

You should have a blower this powerful and easy to use.

The Optimax Concept

- Optimum performance / Maximum output from our aerodynamic fan and housing
- Controllable airflow from our split stream deflector makes you more productive
- Solid construction stands up to your everyday work conditions



Redesigned From The Base Up

We started with a simple objective: improve the world's most productive wheeled blower by making it easier to use and more durable than ever. The result is that the new Optimax blowers set a new standard in performance and ease of use.



Fans

Reverse angle steel fans provide power. These fans are stronger than ever, built with the advanced welding technology. The blades are stamped from a single piece of 10 gauge steel and then welded to the hub with a precision robot to create a solid connection. The 27occ and larger fans are dual plane balanced to tighter tolerance—to reduce stress and vibration.



Steel scrolled housing.

Optimal Control

Shaping the inlet air allows us to deliver a smoother less turbulent output. Splitting the output air into 2 streams keeps debris under control. Adjust the chute for the conditions and job at hand quickly and easily, then let the blower do the work. Even our discharge chute is low and wide—to provide a more effective air pattern.



Solid Connections, Rugged Design

Continuously welded housing, a 1 piece lower deck, single tubular lower frame, 2 bolts for the upper handle connection all show the importance we placed on a machine that lasts.

Maximize Performance for Your Job

Each job is different and the conditions change with the weather. There are days when you need to peel wet leaves off the ground, and other times when you want to keep leaves low so the wind doesn't take them away. Set the exclusive Little Wonder split stream deflector for your job, and gain control.



Remote Control Deflector

- · Put the powerful airflow to work.
- Locking knob and chain drive that reduces stress on the cable.




Built in front discharge.





Little Wonder's Larger & Lower Chute Gives You Better Blowing Power

The Little Wonder discharge chute on our LB270 Subaru model is nearly twice as large at 25 square inches as some competitive models of the same horsepower, plus the bottom of the air steam is located just two inches off the ground so there is no need to constantly adjust or redirect the air stream.



LITTLE WONDER

25 sq. inch square chute | 2" off the ground



COMPETITOR

13 sq. inch round chute | 5" off the ground

Full Line OPTIMAX

Different Platforms But Common Features.

We recognize different uses and different sized jobs, but didn't sacrifice quality when we made our smallest models

160 & 170cc Push Models Are Optimax In Smaller Size

- · Smaller package, powerful performance
- Rugged design
- Improved balance on the 160/17occ models with 10" tires





- Larger models deliver more productivity
- Deeper fans & larger housings
- · Remote control airflow
- Larger fan depth allows 2 plane balancing



Self Propelled Models - 270-570cc

- Adapts to conditions like you do
- Quick to get to work and then match speed to conditions
- Larger 13" turf tires
- Forward up to 4.1 mph;
 Reverse up to 2.5 mph



Distributor



Asphalt Brooms

MARSHALLTOWN's Asphalt Broom and Coarse Asphalt Broom both come with a handle included. Our Asphalt Broom has a 24" steel blade scraper and is great for removing ice, snow, construction clean-up, and other compacted debris. The bristle side works as a heavy duty industrial broom and has braces for extra stability and strength. The Coarse Asphalt Broom, also 24", is a brown plastic garage brush used for wet or dry sweeping of rough concrete or asphalt floors. It won't soften when exposed to water or oils. Both brooms are Made in the USA with Global Materials.

Coarse Asphalt Broom

- Coarse 24" (610mm) brown plastic garage brush used for wet or dry sweeping of rough concrete or asphalt floors
- · Will not soften when exposed to water or oils
- 1¹/s" X 60" (28mm X 1524mm) threaded handle included



Asphalt Broom

 24" (610mm) attached steel blade scrapes and removes ice, snow, construction clean-up and other compacted debris

 Conveniently turns over to convert to a heavy duty 24" (610mm) wide industrial sweeping broom

 Braces provide extra stability and strength

Handle included



Distributor

Brewer Cote of Arizona "The Pavement Maintenance Specialists"
5226 West Missouri Avenue, Glendale Arizona 85301
www.brewercoteaz.com Tel 623-931-3728 toll 888-931-3728 Fax 623-842-0714 sales@brewercoteaz.com



Diesel Engine Powered Pressure Washers

Performance, Durability, Reliability, Serviceability, Long-Term-Low-Cost, Un-Matched

With Vanguard Industrial diesel engines, in **Cold** or **Hot water** versions diesel fired heater, and an attitude Towards removing "that which **must** come off the surface." These systems are modular in design for simplistic configuration, better trailer balance and serviceability. No machine compares in "**Long term low cost**", **Ease of Maintenance**, or **Serviceability**... Our **Engineering** and **Service** departments **work together**. You will be **Impressed**, **Long-term**.

Beckett Burners provide the heat to the Industries most efficient heaters in their Class. These Modular configurations have the most accurate controls and safety devices in this industry

Reliable, easy starting – industrial duty Vanguard-Daihatsu Diesel engines come with low oil shut down, overheat protection and a solid 2 year Warrantee Cabinetry in optional... Ultra-Quiet operation and "severe" weather proofing are available in stainless steel, aluminum, or powder coated steel frame with beefy ABS panels... Have it your way!

All **BullDogPRO™**Frames are Sandblasted,
Primed and Powder
Coated for the look and
durability you want

System is shown with many options and many more are available

We Specialize in Custom Systems

Easy access oil drain for quick oil changes and improved maintenance



Convenient throttle controls and electric start are standard

Beefy Rubber Feet absorb vibration for smooth operation and long life and include mounting hardware

Fuel Cell shown, was a Custom order with quick change manifold fuel cells alloy, are available in dozens of types, shapes and sizes, Plastic and Metals, many with QC's for easy removal

Industrial Grade, heavy duty triplex pump systems with forged brass head, bronze rods, large oil bath and ceramic plungers are all about durability. We add high flow feed lines, high capacity clear bowl filter assembles, free flowing corrosion resistant fittings, and high volume bypass system for abusability. All systems over 7 gpm incorporate dual pumps, for durability, lower cost seal kits, and easier to feed fluid dynamics all lend to longer term lower cost.

COLD VERSIONS	GPM	PSI	НР	HOSE
SCD 5 - 4000	5.0	4000	18	50 ft R2
SCD 5 - 4000	5.0	4000	18	50 ft R2
SCD 6.5 - 4000	6.5	4000	23	50 ft R2
SCD 5 - 5000	5.0	5000	23	50 ft R2
SCD 7 – 4000	7.0	4000	26	50 ft R2
SCD 7 - 5000	6.5	4000	26	50 ft R2
SCD 5 - 6000	5.0	6000	26	50 ft R2
SCD 10 - 4000	10.0	4000	34	50 ft R2
SCD 7 - 6000	6.2	6000	34	50 ft R2

HOT VERSIONS	GPM	PSI	HP	HOSE
SHD 4 – 3500	4.0	3500	10	50 ft R2
SHD 5 – 4000	5.0	4000	18	50 ft R2
SHD 6.5 – 4000	6.5	4000	23	50 ft R2
SHD 5 – 5000	5.0	5000	23	50 ft R2
SHD 7 – 4000	7.0	4000	26	50 ft R2
SHD 7 – 5000	6.5	4000	26	50 ft R2
SHD 8 – 4000	8.0	4000	26	50 ft R2
Many other combinations are available Call!				
and They'll run on JP Jet Fuel too!				

Sirocco and VacuBerm are quality products manufactured by Cleaning System Specialists, Inc. dba www.Pressurewasher.net

BullDogPRO Water Blasters......www.PressureWasher.net**

Distributed By

BullDogPho # # WaterBlasters

Cold Water Pressure Washers - Gas Driven Engine

- Reliable Industrial Duty Engines
- 5 year Warranty on all Pumps
- E-Z Pull Starting
- Compact, Efficient & Portable
- Performance Options Available
- Hi-Output Systems Available

 ${\cal BullDogPRO}^{\mbox{
m M}}$ Water Blasters are the toughest pressure washers on the market built specifically for the demands of professional users. Powered by continuous duty Honda, Vanguard or Subaru engines, all ${\cal BullDogPRO}^{\mbox{
m M}}$ Systems feature premium tri-plunger, oil bath pumps plumbed for reliability and long term low cost. For serious cleaning, you need serious equipment. There's only one choice – The ${\cal BullDogPRO}^{\mbox{
m M}}$ Industrial grade, tri plunger, oil bath

High pressure hose is rated to the highest standards for secure cleaning

Ultra-quiet low tone muffles are always helpful. Ask for Kohler or Briggs version

Belt Drive Versions & many other configurations are also available!

Easy pull Trigger gun provides hours of fatique free cleaning

Beefy easy access filter protects pump from damaging debris in the water

90% of Pump failures are due to overheating seals in bypass.... Our 60" Bypass Loop eliminates overheating



All systems powered by ultra-reliable industrial duty Honda, Vanguard, Kohler or Subaru engines

Annovi Reverberi high pressure pump with forged brass head and ceramic

pistons for extra durability and long life

Easy access oil drain plug for quick oil changes and improve maintenance

Convenient lifting bar for easy hoisting of unit into trucks or trailer beds

Rugged 2-ply tubed Pneumatic Tires absorb vibration and maneuver easily on all terrains

Electric Start is Available, and many other Options too! Please Specify for quote!!

For extra Long bypass times ask for the Float Tank Option shown here



Model	GPM	PSI	HP	Hose
PCG 4 - 2500	3.5	2500	7	25 ft R1
PCG 4 - 3200	4.0	3200	9	50 ft R2
PCG 3 - 4000	3.0	4000	9	50 ft R2
PCG 4 - 4000	4.0	4000	13	50 ft R2+
PCG 5 - 4000	5.0	4000	16	50 ft R2+
PCG 4.5 - 4400	4.5	4400	16	50 ft R2+
PCG 5.5 - 4000	5.5	4000	18	50 ft R2+

Also see our Belt Drive versions for up to 7000 psi. Skid mount versions and Heaters are available too.

Sirocco and VacuBerm are quality products manufactured by Cleaning System Specialists, Inc. dba www.Pressurewasher.net

Bull Dog PRO ™ Water Blasters......www.PressureWasher.net

Distributed By

Brewer Cote of Arizona, Inc., 5226 W. Missouri Ave, Glendale, Arizona 85301 www.brewercoteaz.com Tel.623-931-3728 Toll 888-931-3728 Fax 623-842-0714 sales@brewercoteaz.com



#SGV3 Performance Vacuum Reclaim system w/VacuBerm™



Long-Term-Low-Cost is Simple,
Serviceable,
and Performance
for the Dollar...

Our Equipment <u>WORKS</u> so you can do the Job.

SGV3-16 shown with optional surface cleaner

SGV3-16 Engine Driven Vacuum

16 hp Vanguard industrial Engine with electric start, low tone muffler and all the beef...
3006 Tuthill hi-lift vacuum Blower for 350 cfm's to 16"Hg lift!
20" x 36" skid frame with vibration isolators, Hi-flow silencer system,
2 ½" x 5 ft. vacuum connect hoses (hi-temp) with cam lock couplers... nice!!! patents pending!

Waste Tank system

D.O.T approved 30gallon drums
Sand blasted, **primed** <u>and</u> **hi-temp. powder coated**,
with **slide-out** Pre-filters, and **Auto pump** out included.

Vacuum Hoses

50 ft. x 2"i.d. crush resistant Xtra heavy duty with 2" end cuffs and **cam lock** couplers at the waste tank. also available in 75ft or 100ft pieces

SandSnake

4 ft. long sand bags... beefy 30 mil plastic just add the sand, Place end to end to **corral wash water** in parking lot application.

VacuBerm

4 ft. long, abrasion resistant PVC for wash water control Multiple VacuBerms can be connected together Also available, 6 ft. version!

Hard Surface Vac Wand

14" wide "squeegee head", and replaceable squeegee blades. You'll be glad we threw this in. !!!

Sirocco and VacuBerm are quality products manufactured by Cleaning System Specialists, Inc. dba www.Pressurewasher.net

Distributor



Sirocco™ # SGV4-29efi Extreme series Vacuum Reclaim System



shown with optional vacuuming surface cleaner and VacuBerm

...You want 4 hoses reclaiming wash-water from 400 ft in each direction?...
Here it's at HALF PRICE of the competition.
AND twice the efficiency AND half the weight!
..We own the patents.

engine unit on

sories..

\$1292.00

Vertical frame footprint 20"x 23" add

#SGV4-29efi Engine Driven Vacuum with 29/26.5 Hp Kohler EFI industrial engine with electronic Fuel injection, low tone muffler and all the beef...

#4" Sutorbilt hi-lift vacuum blower for 500 cfm's! Hi-flow silencer system,
With Hi-flow silencer system, skid frame with vibration isolators

Waste Tank system

#9270-30WasteTankAPO2

dimensions: 20"dia. x 35"h

2 each

D.O.T approved 30gallon drums, seriously waterproofed.. stainless tanks available!
Sand blasted, **primed** and **multi-stage** powder coated, **stainless** hardware,

with slide-out Pre-filter, and Auto pump out included. (..requires 115vAC 1500 watts)

and 2 each 2.5"x 5 ft. vacuum connect hoses (hi-temp) and cam lock couplers.

Vacuum Hose 100 ft. x 2"i.d. crush resistant Xtra heavy duty #7300-200V/100-RD 1 each with 2" end cuffs and cam lock couplers at the waste tank. also available in 75ft or 100ft pieces

SandSnakes 3ea 4 ft. and 3ea 18" long sand bags.. beefy 30 mil plastic #SandSnake18, 48 6 each just add the sand, and place end to end to corral wash water in parking lot application.

#SiltFilter48 48" & 24" fiber pad keeps your VacuBerm from being clogged by sand 2 each

#PuddleSucker This 8" square reclaim tool can suck up to 40gpm ..easily.

1 each

*ChokerValve This keeps one tool from leaching all the suction from another tool in use.

1 each

Hard Surface Vac Wand 14" wide "squeegee head", # 9406-HSVwand 1 each and replaceable squeegee blades.. You'll be glad we threw this in.! with the 2" hose cuff x tool adapter.

VacuBerm #VacuBerm48

4 ft. long, abrasion resistant PVC for wash water control

Multiple VacuBerms can be connected together. 6 ft. version also available! \$249.

Distributor



Replacement Brushes

Brushes for all makes and models of sweepers.

FEATURES:

- rugged poly, wire, and combination sections available
- replacement brushes to fit your job requirements
- sections, strip brooms, tube brooms, and gutter broom from Sweepster are cost efficient for all your sweeping needs



The Power of Combined Excellence



Convoluted & Flat Wafers

Polypropylene



Excellent for all types of sweeping, our high quality poly brushes have superior flicking action, for excellent material movement and clean sweeping. The polypropylene brushes are easy on all surfaces.

Wire



Wire wafers are generally used with polypropylene wafers to make poly/wire brushes. They are perfect for gravel, loose stone, and dirt - wherever heavy-duty cleaning is needed.

Dual-plane crimping and no break wire give maximum, long lasting strength.

Combination



Sweepster's multi-purpose combination poly/ wire brushes give you the versatility of poly and strength of wire in one section, at an affordable price.

Sweeper	er Dlameter		Wafers per Set		
brand/model	Inside	outside	flat	convoluted	
Athey/Mobil	10"	36*	36	30/2F	
Balderson 9'	7 1/8"	24"	60	n/a	
Bobcat 54*	6 3/8"	21 3/8"	34	32	
Bobcat 60°	6 3/8"	21 3/8"	37	35	
Bobcat 72*	6 3/8"	21 3/8"	44	42	
68" Angle Broom	6 3/8"	21 3/8"	41	39	
Broce 7'	10"	32"	47	41	
Broce 8'	10"	32"	54	48	
Elgin Eagle	10"	36*	37	3 1/2F	
Eigin Pelican	10°	36*	40	34/2F	
Elgin Pelican	10 5/8"	36"	40	n/a	
Lay-Mor 3'	6 3/8"	24"	24	21	
Lay-Mor 4'	6 3/8"	24*	28	25	
Lay-Mor 6'	6 3/8"	24"	41	39	
Lay-Mor 8'	6 3/8"	24"	56	49	
MB 5	10"	32"	35	30	
MB 6"	10"	32"	41	36	
MB 7"	10"	32"	48	42	
MB 8"	10°	32"	55	48	
MB Cub	6 3/8"	24"	28	25	
MB 6" Cub	6 3/8"	24"	43	39	
Roscoe 7'	10"	32"	48	42	
Roscoe 8"	10"	32"	55	48	
Shawnee 7'	10"	32"	48	41	
Sweepster C36	6 3/8"	24"	23	20	
Sweepster 4"	6 3/8"	24°	28	24	
Sweepster 5'	6 3/8"	24"	35	31	
Sweepster 5'	10"	32"	34	29	
Sweepster 6'	6 3/8"	24"	42	39	
Sweepster 7"	10"	32"	47	42	
Sweepster 8"	10"	32"	54	47	
Waldon SwpMaster		32"	54	47	
Waldon VersaSwp	10"	32"	54	47	
WH/Allmand 6600	10°	32"	50	43	
WH/Allmand 6300	10"	32"	50	43	
Specifications and design				and without lability	

Specifications and design are subject to change without notice and without liability therefore, whenever applicable specifications are in accordance with SAE standard.

The Industry Standard for Replacements

Tube Brooms

- spiral wrapped, abrasion resistant, and impervious to grease and oil
- 12" to 36" diameters available to fit all popular sweepers



Model	OD
Athey/Mobil	36*
Eigin Pelican	36*
Eligin White Wing	36
Eigin Eagle	36"
Elgin Crosswind	10.5*
Eigin Whiriwind	16*
Elgin Geovac	14.5*
FMC/Wayne	36*
FMC/Wayne Vanguar	rd 32°
Gravely	18*
Johnston 400	12*
Johnston 505	12*
Johnston 600	16*
Johnston 605	16*
Johnston Vanguard	32*
MB Angle Brooms	16" & 19"
Murphy/MB Cruiser	36*
Steiner	16"
Tennant 830	23*
Tymco 600	12"
Vac-All	16*

Hand Brooms

- heavy-duty street & garage brooms
- available in various sizes
- various brush options available to fit your job requirements from dust to small stone



Auger Brushes

 specific brushes for grain handling



Industrial Tubes

 quality spiral wrap tubes for Tennant, FMC, Mobile, Wayne, Powerboss, Eigin, and Advance



Strip Brooms

- provides flexible poly refilis for your main broom
- quick & economical way to keep your sweeper on the road

Model	Longth	Malabi
Model	Length	
Eigin Eagle	60°	13*
Eigin Pelican	66*	13*
Athey/Mobil	58*	13*
Vanguard	56.5°	13°
Sweepster Ang	gle Broom	8
5ft	56*	11"
6ft	68*	11"
7ft	80*	11"
8ft	92"	11"
Waldon 8ft	88*	11"
Broce 8ft	91"	11"
Push/Flat Broo	ome	
4ft	48"	11"
5ft	60°	11"
6ft	72"	11"
7ft	84*	11"
8ft	96"	11"

Specialty Strip Brooms - Concrete & speciality strips up to 22 feet. Call 800.456.7100

Specifications and design are subject to change without notice and without liability, therefore, whenever applicable specifications are in accordance with SAE standards.

Gutter Brooms



FEATURES:

- tough and versatile
- easy change bolt-on, snap-on, or woodbacks
- filled with high quality oil-tempered wire
- available for all makes and models

Brand	Model	Description	Brand	Model	Description
Aaplex	44 Magnum	4 segment bolt-on	Murphy	all models	7 segment woodback
	7000	5 segment bolt-on	The second second		12 segment snap-on
Athey	all models	4 segment bolt-on	Peabody/Myers	Alpha 350	4 segment bolt-on
1000		7 segment wood back		Alpha 550	4 segment boit-on
		10 segment snap-on	Sweeprite	1100	4 segment boit-on
Ecolotec	Mark III/IV	10.5" woodback	WINNESS TO	2200	4 segment bolt-on
		13" woodback		4400	4 segment boit-on
		13" woodback poly	Sweepster	HB60/72	steel or poly bristles
		18" woodback		SB48/60/72	poly bristles
Elgin	Crosswind	4 segment bolt-on	1	HBA	steel or poly bristles
	Eagle	5 segment bolt-on		TR48	poly bristles
	Pelican	4 segment bolt-on	2000	TP60	steel or poly bristies
	Trailwind	16* woodback	Tennant	Centarion	5 segment bolt-on
	Whirtwind/Crosswd	16" woodback	Tymco	210	sloped poly wafer
	Whitewing	4 segment bolt-on			sloped wire wafer
FMC	900 Series (3 wheel)	11 segment snap-on		210 (optional)	4 segment bolt-on
	Vanguard 3000	12 segment snap-on		600	4 segment bolt-on
	Vanguard 4000	12 segment snap-on	AND DESCRIPTION OF THE PERSON	FHD	4 segment bolt-on
	optional (all models)	4 segment bolt-on	VacAII	all models	18" woodback
	model 12	7 segment snap-on		E10	3 segment bolt-on
Johnston	all models	13° woodback	Wayne	900 Series	4 segment bolt-on
		16" woodback		(3 & 4 wheel)	11 segment snap-on
		18" woodback			
MB	Cruiser	7 segment wood 34"			
		7 segment wood 30°			
		12 segment snap-on			

Distributor
Brewer Cote of Arizona
The Pavement Maintenance Specialists
5226 W Missouri Avenue, Glendale, AZ 85301
www.brewercoteaz.com
888-931-3728
sales@brewercoteaz.com



WSP24 Walk Behind Sweeper



Features

24" (60cm) Wide Brush makes fast work of large areas
14" (350mm) Diameter Brush Sweeps up to 5" (15cm) deep material
133 lbs. Lightweight for easy handling
Self-Propelled for easy Operation
One Forward and One Reverse Speed
Adjustable handle for comfortable Operation
Easy to Operate Clutch for Brush and Traction Control
Brush Angles easily from Handle Bars
Big 3.00 x 4 Tires for traction in Snow & on Turf
Ground Speed 2 mph (3 kmh) covers large areas quickly
350 rpm brush Speed sweeps large accumulators of snow, thatch and debris

Distributor

Brewer Cote of Arizona "The Pavement Maintenance Specialists"
5226 W Missouri Avenue, Glendale, AZ 85301
www.brewercoteaz.com Tel 623-931-3728 Toll 888-931-3728 Fax 623-842-0714 sales@brewercoteaz.com



WSP36 Multi Speed Walk Behind Sweeper



Features

67"L x 42"W x 35"H - 274 lbs.

Infinitely Adjustable Angling from 20" Right & Left for variable conditions

Powerful Honda OHV 6XV16 Engine - Meets EPA SNRE PH2 2007 & CARB Tier 2 2006 Criteria

Two Brush Speed ranges for variable conditions

Five forward Speeds, Neutral and Reverse

Differential Drive for Two-Wheel traction and ease of turning

Complete Fill Brush for no-streak sweeping

Balanced Unit eliminates need for casters to sweep

Solid handle Bars with cushioned grips for comfortable operation

Brush Hood covers 125" arch

Powder-Coated for durability

Distributor

Brewer Cote of Arizona The Pavement Maintenance Specialists
5226 W Missouri Avenue, Glendale, AZ 85301
www.brewercoteaz.com 623-931-3728 888-931-3728 623-842-0714 sales@brewercoteaz.com