

BREWER COTE [®]

The Pavement Maintenance Specialists of Arizona
Est 1979



Skid Mounted Heated Emulsion Sprayer

FEATURES

- * 5' Aluminum spray wand with 35 1/2 " hose
- * Round "U" bottom for easy cleaning & 3' drain
- * Gear pump rated minimum 10 gal per minute
- * Circulation and bypass control for wand pressure
- * Large 16" lockdown removable manway
- * 20 lb propane tank, regulator and pressure gauge
- * 150,000 btu propane burner, removable hand torch
- * Honda Engine with 6:1 gear reduction drive
- * Lower engine speed means longer pump life
- * 8 gal flush tank for clean out of pump and wand
- * 3" heat tube, vented to haet pump (pump enclosed)

OPTIONS

- * Electric Ignition
- * Electric Start Engine
- * Electric Water Pump
- * Electric Burner (12v from vehicle battery)
- * Electric Brakes
- * Propane Engine
- * Larger propane tanks
- * 6' Spray bar with 5 tips
- * Hose Reels
- * 5/16" ball pintle hitch
- * Additional flush tank

SKID MOUNTED UNIT SPECIFICATIONS

Model QS/E	250 gal
Height	4"
Length	7'6"
Width	3'6"
Weight	850 lbs

Pump Specifications

1" Positive Displacement Gear Pump
1 yr Manufacturer's Warranty

Engine Specifications

GX Honda Engine with 6:1 gear reduction
36 mo Manufacturer's Warranty

5226 W. Missouri Avenue Glendale Arizona 85301
www.brewercoteaz.com 888-931-3728 sales@brewercoteaz.com