

OIL SPOT PRIMER



Brewer Cote® Oil Spot Primer is a modified latex acrylic that has been formulated To help Pavement Sealers adhere to existing stained surfaces. Added ingredients improve the penetrating ability of our primer and thus gives added future protection. For use on all Parking Lots, Aprons and Driveways of asphalt construction.

METHOD OF APPLICATION

Stir well before using, Apply a thin coat. Should be diluted up to 100% with water. May be Brushed or sprayed with a garden type sprayer. Always torch lightly the spot and scrape off Excess oil before applying.

WEATHER LIMITATIONS

For best results, apply on cleaned, dry surfaces when temperature are not to drop below 50° F for 2 hrs.

Drying time	Clean up	Color	Packing
1 hr. or less depending on weather conditions	Water when wet mineral spirits when dry	Dark Brown when wet Black when dry	5 gal pails (45 lbs.) 55 gal Drums (480 lbs.)

PHYSICAL ANALYSIS

Non-Volatiles %	45% min
Specific Gravity	1.02
Flexibility	No Cracking or Flaking
Resistance to impact	No Chipping, Flaking or Cracking
Accelerated Weathering	No deterioration

BREWER COTE of ARIZONA

THE PAVEMENT MAINTENANCE SPECIALISTS 5226 W. MISSOURI AVENUE, GLENDALE, AZ 85301
www.brewercoteaz.com Tel. 623-931-3728 Toll 888-931-3728 Fax 623-842-0714 sales@brewercoteaz.com