

PEC

Paving Equipment Cleaner

Paving Equipment Cleaner is a heavy duty cleaner that can be used on a variety of asphalt related equipment to include:

- Truck Beds
- Racks & Shovels
- Paving Machines
- Rollers & Spreader Bars
- Wheelbarrows

Paving Equipment Cleaner is a ready to use product that can also be used to coat tools and equipment prior to use to keep them free of build-up.

Directions for Use

Spray, wipe or brush the object to be cleaned with PEC.

Small objects may also be immersed, if desired. Allow cleaner to remain on surface until the asphalt is loosened.

Safety Reminder

Consult Product Label and Safety Data Sheet (SDS) before use. Prior to using this or any cleaning product, make sure employees read and understand the hazard information found on the product label and Safety Data Sheet (SDS). The label and SDS will also provide information on handling precautions, protective equipment and first aid instructions which might be appropriate for this product.



Technical Specifications

Appearance	Clear Liquid
Odor	Slight odor
pH	N/D
Foaming	None
Flash Point	159.8F
Rinsability	Complete
Stability/Storage	2 Years
Emulsification	Complete
Solubility	100%
Phosphate Content	None

Product Number

- G9-4CS
- G9-5G
- G9-55

Packaging

- 4 Gallon Case
- 5 Gallon Pail
- 55 Gallon Drum

Distributor

Brewer Cote of Arizona The Pavement Maintenance Specialists
5226 W Missouri Avenue, Glendale, Arizona 85301
www.brewercoteaz.com 888-931-3728 sales@brewercoteaz.com

SOLVALL

Tar & Asphalt Remover

Solvall is a ready-to-use, water rinsable liquid, which quickly and easily removes coal tar sealer, asphalt sealer, crack sealer, roofing tar, mastic and tack coat from most washable surfaces. Formulated for use on tools, equipment, vehicles, sidewalks, flooring, siding, clothing and carpeting. Will breakdown the composition of the stain and emulsify so that it is rinsed away with water. It is non-foaming and evaporates slowly. SOLVALL will clean up fresh spills, splatters and oversprays, as well as, caked-on messes.

Directions for Use

USAGE: Application and coverage rate will vary depending on conditions. FIRST AND FOREMOST Solvall should be used full strength. For hard surfaces such as concrete, metal, wood, glass, ceramic and stone, the object may be sprayed, poured, brushed, blotted or soaked. Allow time for product to work, then agitate with a rag or stiff bristle brush and rinse away stain and residue with water. Repeat as needed. Thicker soils can be scraped to remove heavy deposits prior to application. Tools and equipment must be solvent resistant. NOTE: Objects to be cleaned should first be tested for compatibility, especially on paints and plastics. Do not use on plastic surfaces unless they are solvent resistant.

Safety Reminder

Consult Product Label and Safety Data Sheet (SDS) before use. Prior to using this or any cleaning product, make sure employees read and understand the hazard information found on the product label and Safety Data Sheet (SDS). The label and SDS will also provide information on handling precautions, protective equipment and first aid instructions which might be appropriate for this product.



Technical Specifications

Appearance	Clear Liquid
Odor	Characteristic
pH	N/D
Foaming	None
Flash Point	118.4 F
Rinsability	Complete
Stability/Storage	2 Years
Emulsification	Complete
Solubility	100%
Phosphate Content	None
Product Number	Packaging
G11-QCS	12 Quart Case
G11-4CS	4 Gallon Case
G11-5G	5 Gallon Pail
G11-55	55 Gallon Drum

Distributor

Brewer Cote of Arizona The Pavement Maintenance Specialists
5226 W Missouri Avenue, Glendale, Arizona 85301
www.brewercoteaz.com 888-931-3728 sales@brewercoteaz.com

Solvit

Tar & Asphalt Remover

A d-limonene based heavy duty degreaser & tar remover. Specially formulated with natural citrus based oils. Excellent for all cleaning tasks. Emulsifies and quickly removes grease & grime. Great for use on tools and equipment, flooring, siding and sidewalks.

Directions for Use

USAGE: Application and coverage rate will vary depending on conditions. **FIRST AND FOREMOST** Solvit should be used full strength. For hard surfaces such as concrete, metal, wood, glass, ceramic and stone, the object may be sprayed, poured, brushed, blotted or soaked. Allow time for product to work, then agitate with a rag or stiff bristle brush and rinse away stain and residue with water. Repeat as needed. Thicker soils can be scraped to remove heavy deposits prior to application. Tools and equipment must be solvent resistant. **NOTE:** Objects to be cleaned should first be tested for compatibility, especially on paints and plastics. Do not use on plastic surfaces unless they are solvent resistant.

Safety Reminder

Consult Product Label and Safety Data Sheet (SDS) before use. Prior to using this or any cleaning product, make sure employees read and understand the hazard information found on the product label and Safety Data Sheet (SDS). The label and SDS will also provide information on handling precautions, protective equipment and first aid instructions which might be appropriate for this product.

Distributor

Brewer Cote of Arizona The Pavement Maintenance Specialists

5226 W Missouri Avenue, Glendale, Arizona 85301

www.brewercoteaz.com 888-931-3728 sales@brewercoteaz.com



Technical Specifications

Appearance	Orange Liquid
Odor	Citrus
pH	N/D
Foaming	None
Flash Point	115.4 F
Rinsability	Complete
Stability/Storage	2 Years
Emulsification	Complete
Solubility	100%
Phosphate Content	None

Product Number

G8-QCS

G8-4CS

G8-5G

G8-55

Packaging

12 Quart Case

4 Gallon Case

5 Gallon Pail

55 Gallon Drum

AR-92

Asphalt Release Agent

AR-92 is a water soluble release agent which prevents asphalt from sticking to the sides and bottom of truck beds. Proper application produces a rich foam which allows asphalt loads to easily slide from truck beds when tilted. Will not affect the composition of the asphalt mix.

Directions for Use

AR-92 is dispensed through standard proportioning valves. Standard dilution is 40 parts of water to 1 part AR-92.

Surface treated must be clean of any asphalt accumulation. Apply solution to sides, bed and spreader bar of the truck. For best results, fill truck with asphalt while the coating is still wet.

Safety Reminder

Consult Product Label and Safety Data Sheet (SDS) before use. Prior to using this or any cleaning product, make sure employees read and understand the hazard information found on the product label and Safety Data Sheet (SDS). The label and SDS will also provide information on handling precautions, protective equipment and first aid instructions which might be appropriate for this product.



Technical Specifications

Appearance	Yellow Liquid
Odor	Mild
pH (1% solution, 22°C)	7-8
Foaming	High
Flash Point	None
Rinsability	Complete
Stability/Storage	2 Years
Emulsification	Complete
Solubility	100%
Phosphate Content	None

Product Number

G5-55

Packaging

55 Gallon Drum

Distributor

Brewer Cote of Arizona The Pavement Maintenance Specialists

5226 W Missouri Avenue, Glendale, Arizona 85301

www.brewercoteaz.com 888-931-3728 sales@brewercoteaz.com