



# RAPID SET

**RAPID SET** is a specially blended copolymer emulsion containing fast drying modifiers which enhances asphalt sealers to achieve a faster drying time. **RAPID SET** has a resistance to oils, fuels and grease. Use **RAPID SET** where increased durability is needed, excellent for airport runways and taxi areas, along with all commercial and industrial properties

## Coverage

Mix well before using, add after sealer has been diluted. Use 3 to 5 gal to every 100 gal of concentrated asphalt emulsion, depending on porosity.

**Smooth to medium surfaces:** 2 gal to every 100 gal of concentrated asphalt emulsion.

**Rough to excessively rough surfaces:** 3 to 5 gal to every 100 gal of concentrated. Asphalt emulsion with 2 lbs. additional Sand 60 mesh.

## Method of Application

Add sealer into agitated machine, add water, then slowly mix in **RAPID SET** while agitating. Add any additional sand (4 lbs per gal max.) Mix well before application.

## Weather Limitations

For best results, do not apply on rainy days or when temperature is expected to drop below 45° F during the next 24 hrs. On hot days, pavement shall be pre-dampened with a fog system.

## Drying Time

4 hrs or less at 70°F, 50% humidity, depending on percentage add and application thickness.

**Color**  
Light Brown

**Clean Up**  
Water when wet,  
Bio D ® when dry.

**Packaging**  
5 gal pails  
55 gal drums