



10 Gallon Mini Melter is an economical solution for smaller jobs. It can provide hot material in 20 min or less. It is the stationary version of Our popular MA10 wheeled unit. Both inner and outer tanks are built of heavy 14 gauge. steel. Standard features include temperature gauge with guards, built in hand agitator and a propane bottle platform (bottle not included). It comes with a 50,000 BTU burner, 10' hose regulator, striker, and draw off valve. The kettle is capable of melting up to 600 lbs. of sealant per day.

Specifications

Length - 29" Width - 30" Height - 32"

Capacity - 10-gal Weight - 95 lbs

Distributor

Brewer Cote of Arizona "The Pavement Maintenance Specialists"

5226 W Missouri Avenue, Glendale, Arizona 85301

www.brewercoteaz.com Tel.623-931-3728 Toll 888-931-3728 Fax 623-842-0714 sales@brewercoteaz.com **85**



30-Gal Flex Kettle can provide hot material in 30 min or less. It is built with 14 gauge steel. Standard features include temperature gauge with guard, built in hand agitator, lifting handles, and hinged lid. Comes with a 50,000 BTU burner, 10' hose, regulator, striker, and draw-off valve. The kettle is capable of melting up to 1200 lbs. of sealant per day.

Specifications:

Length - 45", Width - 26", Height - 38"
Capacity 30 Gallon, Weight - 200 lbs.

55 gal Flex Kettle can provide hot material in 30 minutes or less. It is built with 14 ga. steel. Standard features include temperature gauge with guard, built in hand agitator, lifting handles, and hinged lid. Comes with a 50,000 BTU burner, 10' hose, regulator, striker, and draw - off valve. The kettle is capable of melting up to 1800 lbs. of sealant per day.

Specifications:

Length - 49", Width - 30", Height - 43",
Capacity - 55 gallon, Weight - 245 lbs.



SPECIFICATIONS

Length – 45”

Width – 16”

Height – 7”



The **SH-30 Retro-Fit Burner** is specifically designed to replace the conventional torch type burner supplied with most U.S. Built 30 gallon direct fire Melter's manufactured through the last decade. It is also usable in some Chinese built "knock-off" units utilizing a torch type burner (check your unit dimensions for fitment). Simple sheet metal modifications to the torch entry side and bottom of the outer sheet metal surfaces are required for installation. Torch valve, hose and regulator are retained after a simple extension tube and orifice exchange is installed. Units receiving the properly installed modification will yield initial melting and recovery speeds equaling that of factory Soft Heat machines. No more torch assembly to lose and no more blow-outs (metal integrity and a melting chamber free of burnt or charred material is critical in selecting a unit for modification) This update kit presents a cost effective way to experience the revolutionary performance and fuel savings of the next generation crack sealant machines that are Soft Heat.

Brewer Cote of Arizona "The Pavement Maintenance Specialists"

5226 West Missouri Avenue, Glendale Arizona 85301

www.brewercoteaz.com Tel 623-931-3728 Toll 888-931-3728 Fax 623-842-0714 sales@brewercoteaz.com



SPECIFICATIONS

Length – 17”
Width – 15”
Height – 7”
Weight – 17 lbs.

The **SH-10 Retro-Fit Burner** is specifically designed to replace the conventional torch type burner supplied with most U.S. Built MA10 Melter / applicators and 10 gal. mini Melter's. It is also usable in some Chinese built "knock-off" units utilizing a torch type burner (check your unit dimensions for fitment). Simple sheet metal modifications to the front and rear of the outer sheet metal surfaces are required for installation. Torch valve, hose and regulator are retained after a simple orifice ex-change. Units receiving the properly installed modification will yield initial melting and recovery speeds equaling that of factory Soft Heat machines. No more torch assembly to lose and no more blow-outs (metal integrity and a melting chamber free of burnt or charred material is critical in selecting a unit for modification) This modification kit presents a cost effective way to experience the revolutionary performance and fuel savings of the next generation crack sealant machines that are Soft Heat.

Brewer Cote of Arizona "The Pavement Maintenance Specialists"
5226 West Missouri Avenue, Glendale Arizona 85301

www.brewercoteaz.com Tel 623-931-3728 Toll 888-931-3728 Fax 623-842-0714 sale@brewercoteaz.com



MA10 Melter/Applicator is a fast and efficient method for the application of hot applied crack sealants. It can also apply materials from stationary kettles or any large Melter. It can be used without heat for cold pour materials. It is capable of melting and applying 600 lbs. of sealant per day.

MA10 is the result of over 25 yrs. of experience in the manufacture and design of Melter applicators. Both inner and outer tanks are built of heavy 14- gauge steel. Standard features include temperature gauge with guards, built in hand agitator, 1/4" thick steel wheels, propane bottle platform, (bottle not included), spring loaded hand-controlled release valve, 3" steel screed, and a stop plate to prevent "stringers" at the end of a run. It comes with 50,000 BTU burner, 6' hose, regulator, and striker.

Specifications

Length - 47", Width - 27", Height - 36",
Capacity - 10-gal , Weight 130 lbs.

Distributor

Brewer Cote of Arizona "The Pavement Maintenance Specialists"
5226 W Missouri Avenue, Glendale, Arizona 85301

www.brewercoteaz.com Tel.623-931-3728 Toll 888-931-3728 Fax 623-842-0714 sales@brewercoteaz.com