



Brewer Flex® Cold Pour Crack Sealant

Brewer Flex® Cold Pour Crack Sealant has been designed with additional Acrylic and Plasticizers to give you Maximum Elongation and Resiliency in a ready to use product. Like our “Brewer Flex® Hot Pour Crack Sealant”, no other product performs as well in both Concrete and Asphalt crack joints.

Use Brewer Flex® Products when you want superior long-lasting results.

ADVANTAGES

- Ready to use • Cost Effective • No Heating Necessary • Flex at Low Temperature
- Great for Hot Climates • Beautifies your Pavement Investment • Extends Life of Pavement

METHOD OF APPLICATION

Stir before using, pour along crack out of the container or applicator. A second application maybe necessary in deep cracks or joints.

WEATHER LIMITATIONS

Do not apply if below 45° F, or if rain is imminent, and is not going to fall below 45° for the next 24 hrs. Pavement slots must be free of dust, dirt and water prior to application. Use compressed Air before applying sealant. Slot may be slightly damp to help penetration of sealant.

COVERAGE

Approximately 30 Ln/ ft. per gal. based on ½” wide by ½” deep cracks. Coverage will vary depending on width / depth of slot and type of application method.

DRYING TIME

For best results, apply to clean dry cracks when temperature is not expected to drop below 50° F for the 24 hrs.

CLEAN UP

Water prior to drying
Use Biodegradable Prism
or suitable solvent

COLOR

Black

PACKAGING

5 gal. pails

BREWER COTE of ARIZONA® INC

“THE PAVEMENT MAINTENANCE SPECIALISTS” 5226 W. MISSOURI AVENUE, GLENDALE AZ 85301
www.brewercoteaz.com Tel. 623-931-3728 Toll 888-931-3728 Fax 623-842-0714 sales@brewercoteaz.com